

# SEALANTS USAGE CALCULATOR

## RUNNING METER PER 300ML CARTRIDGE

	WIDTH (mm)												
DEPTH (mm)	2	3	4	5	8	10	12	15	20	25	30	40	50
2	75.0	50.0	37.5	30.0	18.8	15.0	12.5	10.0	7.5	6.0	5.0	3.8	3.0
3	50.0	33.3	25.0	20.0	12.5	10.0	8.3	6.7	5.0	4.0	3.3	2.5	2.0
4	37.5	25.0	18.8	15.0	9.4	7.5	6.3	5.0	3.8	3.0	2.5	1.9	1.5
5	30.0	20.0	15.0	12.0	7.5	6.0	5.0	4.0	3.0	2.4	2.0	1.5	1.2
6	25.0	16.7	12.5	10.0	6.3	5.0	4.2	3.3	2.5	2.0	1.7	1.3	1.0
8	18.8	12.5	9.4	7.5	4.7	3.8	3.1	2.5	1.9	1.5	1.3	0.9	0.8
10	15.0	10.0	7.5	6.0	3.8	3.0	2.5	2.0	1.5	1.2	1.0	0.8	0.6
15	10.0	6.7	5.0	4.0	2.5	2.0	1.7	1.3	1.0	0.8	0.7	0.5	0.4
20	7.5	5.0	3.8	3.0	1.9	1.5	1.3	1.0	0.8	0.6	0.5	0.4	0.3

## RUNNING FEET PER 300ML CARTRIDGE

	WIDTH (mm)												
DEPTH (mm)	2	3	4	5	8	10	12	15	20	25	30	40	50
2	246.1	164.0	123.0	98.4	61.5	49.2	41.0	32.8	24.6	19.7	16.4	12.3	9.8
3	164.0	109.4	82.0	65.6	41.0	32.8	27.3	21.9	16.4	13.1	10.9	8.2	6.6
4	123.0	82.0	61.5	49.2	30.8	24.6	20.5	16.4	12.3	9.8	8.2	6.2	4.9
5	98.4	65.6	49.2	39.4	24.6	19.7	16.4	13.1	9.8	7.9	6.6	4.9	3.9
6	82.0	54.7	41.0	32.8	20.5	16.4	13.7	10.9	8.2	6.6	5.5	4.1	3.3
8	61.5	41.0	30.8	24.6	15.4	12.3	10.3	8.2	6.2	4.9	4.1	3.1	2.5
10	49.2	32.8	24.6	19.7	12.3	9.8	8.2	6.6	4.9	3.9	3.3	2.5	2.0
15	32.8	21.9	16.4	13.1	8.2	6.6	5.5	4.4	3.3	2.6	2.2	1.6	1.3
20	24.6	16.4	12.3	9.8	6.2	4.9	4.1	3.3	2.5	2.0	1.6	1.2	1.0